



UL Style 1028

PVC Insulated Wire For Appliance Hook-up Use

Description:

Conductor: Stranded Soft Bare or Tinned Copper

Insulation: PVC

Characteristics:

Rating Temperature: 105°C

Rating Voltage : 600 V. AC

UL VW-1 & CSA FT1, FT2 Flame Test Approved

UL Oil Resistant Test at 60°C Approved

Applications:

For Internal Wiring of Appliances

Construction:



UL/CSA	Rating		Size	Conductor	PVC Insulation		Dielectric Voltage	Standard Length		
	Style No.	Max. Volt.			Max. Temp.	AWG or MCM		No./mm	Thickness Min. Avg. mm	Approx. O.D. mm
1028	600V	105°C	20	11/0.250	1.143	3.45	2.0	328	100	Coil
			18	17/0.250	1.143	3.7	2.0	328	100	Coil
			16	26/0.254	1.143	4.0	2.0	328	100	Coil
			14	41/0.254	1.143	4.4	2.0	328	100	Coil
			12	65/0.254	1.143	4.87	2.0	328	100	Coil
			10	104/0.254	1.143	5.5	2.0	328	100	Coil
			8	165/0.254	1.143	6.7	2.0	328	100	Coil
			6	263/0.254	1.524	8.8	2.0	328	100	Coil