



UL Style 1284

PVC Insulated Wire For Appliance Hook-up Use

Description:

Conductor: Stranded Soft Bare or Tinned Copper

Insulation: PVC

Characteristics:

Rating Temperature: 105°C

Rating Voltage : 600 V. AC

UL VW-1 & CSA FT1, FT2 Flame Test Approved

UL Oil Resistant Test at 60°C Approved

Applications:

For Internal Wiring of Appliances

Construction:



UL/CSA	Rating		Size AWG or MCM	Conductor No./mm	PVC Insulation		Dielectric Voltage KV/1 min.	Standard Length		
	Max. Volt.	Max. Temp.			Thickness Min.Avg. mm	Approx. O.D. mm		FT	M	Packing
1284	600V	105°C	8	165/0.254	2.032	8.6	2.0	328	100	Coil
			6	263/0.254	2.032	9.6	2.0	328	100	Coil
			4	417/0.254	2.032	11.0	2.0	328	100	Coil
			2	664/0.254	2.032	12.7	2.0	328	100	Coil
			1	837/0.254	2.032	14.1	2.5	328	100	Coil
			1/0	1056/0.254	2.032	15.2	2.5	328	100	Coil
			2/0	1331/0.254	2.032	16.6	2.5	328	100	Coil
			3/0	1678/0.254	2.032	18.0	2.5	328	100	Coil
			4/0	2116/0.254	2.032	19.8	2.5	328	100	Coil
			250 MCM	2507/0.254	2.413	21.8	3.0	328	100	Coil
			300	3000/0.254	2.413	23.3	3.0	328	100	Coil
			350	3494/0.254	2.413	24.8	3.0	328	100	Coil
			400	4007/0.254	2.413	26.1	3.0	328	100	Coil
			450	4500/0.254	2.413	27.4	3.0	328	100	Coil
			500	4993/0.254	2.413	28.6	3.0	328	100	Coil
			550	5507/0.254	2.794	29.8	3.5	328	100	Coil
600	6000/0.254	2.794	30.8	3.5	328	100	Coil			