



# UL Style 1650

## PVC Insulated Wire

### Description:

Conductor: Stranded Soft Bare or Tinned Copper

Insulation: PVC

Characteristics:

Rating Temperature: 105°C

Rating Voltage : 600 V. AC

UL VW-1 & CSA FT1, FT2 Flame Test Approved

UL Oil Resistant Test at 60°C Approved

### Applications:

For Internal Wiring of Appliances

### Construction:



| UL/CSA | Rating    |            | Size | Conductor  | PVC Insulation |            | Dielectric Voltage | Standard Length |                        |                 |
|--------|-----------|------------|------|------------|----------------|------------|--------------------|-----------------|------------------------|-----------------|
|        | Style No. | Max. Volt. |      |            | Max. Temp.     | AWG or MCM |                    | No./mm          | Thickness Min. Avg. mm | Approx. O.D. mm |
| 1650   | 600V      | 105°C      | 4    | 417/0.254  | 1.524          | 9.9        | 2.0                | 328             | 100                    | Coil            |
|        |           |            | 2    | 664/0.254  | 1.524          | 11.6       | 2.0                | 328             | 100                    | Coil            |
|        |           |            | 1    | 837/0.254  | 1.982          | 14.0       | 2.5                | 328             | 100                    | Coil            |
|        |           |            | 1/0  | 1056/0.254 | 1.982          | 15.1       | 2.5                | 328             | 100                    | Coil            |
|        |           |            | 2/0  | 1331/0.254 | 1.982          | 16.5       | 2.5                | 328             | 100                    | Coil            |
|        |           |            | 3/0  | 1678/0.254 | 1.982          | 17.9       | 2.5                | 328             | 100                    | Coil            |
|        |           |            | 4/0  | 2116/0.254 | 1.982          | 19.8       | 2.5                | 328             | 100                    | Coil            |