



UL Style 2464

PVC Jacketed Cable

Description:

Conductor: Stranded Soft Bare or Tinned Copper

Insulation: PVC

Core Number: Two or More Core

Shield: Optional

Jacket: PVC

Characteristics:

Rating Temperature: 80°C

Rating Voltage : 300 V. AC

UL VW-1 Flame Test Approved

UL Oil Resistant Test at 60°C Approved

Use: Internal Wiring or External Interconnection of Electronic Equipment

Construction:



UL/CSA	Rating		Size	Conductor	PVC Insulation		Assembly	PVC Jacket		Standard Length		
	Style No.	Max. Volt.			Max. Temp.	AWG or MCM		No./mm	Thickness Min. Avg. mm	Approx. O.D. mm	Core/No.	Thickness Min. Avg. mm
2464	300V	80°C	20	11/0.250	0.762	2.7	2C	0.762	7.1	328	100	Coil
			18	17/0.250	0.762	2.9	2C	0.762	7.5	328	100	Coil
			16	26/0.254	0.762	3.2	2C	0.762	8.1	328	100	Coil
			14	41/0.254	0.762	3.6	2C	0.762	8.9	328	100	Coil
			12	65/0.254	0.762	4.1	2C	0.762	9.9	328	100	Coil
			10	104/0.254	0.762	4.7	2C	0.762	11.1	328	100	Coil
			8	165/0.254	1.143	6.7	2C	0.762	15.1	328	100	Coil
			6	263/0.254	1.524	8.5	2C	0.762	18.7	328	100	Coil
			4	417/0.254	1.524	9.9	2C	1.143	22.3	328	100	Coil
			2	664/0.254	1.524	11.6	2C	1.143	25.7	328	100	Coil
			1	837/0.254	2.032	14.1	2C	1.524	31.5	1000	305	Reel
	1/0	1056/0.254	2.032	15.2	2C	1.524	33.7	1000	305	Reel		
	2/0	1331/0.254	2.032	16.6	2C	1.524	36.5	1000	305	Reel		
2464	300V	80°C	20	11/0.250	0.762	2.7	3C	0.762	7.5	328	100	Coil
			18	17/0.250	0.762	2.9	3C	0.762	7.9	328	100	Coil
			16	26/0.254	0.762	3.2	3C	0.762	8.6	328	100	Coil
			14	41/0.254	0.762	3.6	3C	0.762	9.4	328	100	Coil
			12	65/0.254	0.762	4.1	3C	0.762	10.5	328	100	Coil
			10	104/0.254	0.762	4.7	3C	0.762	11.8	328	100	Coil
			8	165/0.254	1.143	6.7	3C	0.762	16.1	328	100	Coil
6	263/0.254	1.524	8.5	3C	1.143	20.8	328	100	Coil			



UL Style 2464

PVC Jacketed Cable

UL/CSA	Rating		Size AWG or MCM	Conductor No./mm	PVC Insulation		Assembly Core/No.	PVC Jacket		Standard Length		
	Max. Volt.	Max. Temp.			Thickness Min.Avg. mm	Approx. O.D. mm		Thickness Min.Avg. mm	Approx. O.D. mm	FT	M	Packing
2464	300V	80°C	4	417/0.254	1.524	9.9	3C	1.143	23.8	328	100	Coil
			2	664/0.254	1.524	11.6	3C	1.143	27.4	328	100	Coil
			1	837/0.254	2.032	14.1	3C	1.524	33.6	1000	305	Reel
2464	300V	80°C	20	11/0.250	0.762	2.7	4C	0.762	8.2	328	100	Coil
			18	17/0.250	0.762	2.9	4C	0.762	8.7	328	100	Coil
			16	26/0.254	0.762	3.2	4C	0.762	9.4	328	100	Coil
			14	41/0.254	0.762	3.6	4C	0.762	10.4	328	100	Coil
			12	65/0.254	0.762	4.1	4C	0.762	11.6	328	100	Coil
			10	104/0.254	0.762	4.7	4C	0.762	13.0	328	100	Coil
			8	165/0.254	1.143	6.7	4C	0.762	17.9	328	100	Coil
			6	263/0.254	1.524	8.5	4C	1.143	23.1	328	100	Coil
			4	417/0.254	1.524	9.9	4C	1.143	26.4	328	100	Coil
2464	300V	80°C	2	664/0.254	1.524	11.6	4C	1.524	31.3	1000	305	Reel
			1	837/0.254	2.032	14.1	4C	1.524	37.3	1000	305	Reel
			20	11/0.250	0.762	2.7	5C	0.762	9.0	328	100	Coil
			18	17/0.250	0.762	2.9	5C	0.762	9.5	328	100	Coil
			16	26/0.254	0.762	3.2	5C	0.762	10.3	328	100	Coil
			14	41/0.254	0.762	3.6	5C	0.762	11.4	328	100	Coil
			12	65/0.254	0.762	4.1	5C	0.762	12.8	328	100	Coil
			10	104/0.254	0.762	4.7	5C	0.762	14.4	328	100	Coil
			8	165/0.254	1.143	6.7	5C	1.143	20.6	328	100	Coil
2464	300V	80°C	6	263/0.254	1.524	8.5	5C	1.143	25.5	328	100	Coil
			4	417/0.254	1.524	9.9	5C	1.524	30.0	1000	305	Reel
			20	11/0.250	0.762	2.7	6C	0.762	9.8	328	100	Coil
			18	17/0.250	0.762	2.9	6C	0.762	10.4	328	100	Coil
			16	26/0.254	0.762	3.2	6C	0.762	11.3	328	100	Coil
			14	41/0.254	0.762	3.6	6C	0.762	12.5	328	100	Coil
			12	65/0.254	0.762	4.1	6C	0.762	14.0	328	100	Coil
			10	104/0.254	0.762	4.7	6C	0.762	15.8	328	100	Coil
			8	165/0.254	1.143	6.7	6C	1.143	22.6	328	100	Coil
2464	300V	80°C	6	263/0.254	1.524	8.5	6C	1.524	28.8	328	100	Coil
			4	417/0.254	1.524	9.9	6C	1.524	33.0	1000	305	Reel
			20	11/0.250	0.762	2.7	7C	0.762	9.8	328	100	Coil
			18	17/0.250	0.762	2.9	7C	0.762	10.4	328	100	Coil
			16	26/0.254	0.762	3.2	7C	0.762	11.3	328	100	Coil
2464	300V	80°C	14	41/0.254	0.762	3.6	7C	0.762	12.5	328	100	Coil
			12	65/0.254	0.762	4.1	7C	0.762	14.0	328	100	Coil
			10	104/0.254	0.762	4.7	7C	0.762	15.8	328	100	Coil



UL Style 2464

PVC Jacketed Cable

UL/CSA	Rating		Size	Conductor	PVC Insulation		Assembly	PVC Jacket		Standard Length		
	Style No.	Max. Volt.			Max. Temp.	AWG or MCM		No./mm	Thickness Min. Avg. mm	Approx. O.D. mm	Core/No.	Thickness Min. Avg. mm
2464	300V	80°C	10	104/0.254	0.762	4.7	7C	0.762	15.8	328	100	Coil
			8	165/0.254	1.143	6.7	7C	1.143	22.6	328	100	Coil
			6	263/0.254	1.524	8.5	7C	1.524	28.8	328	100	Coil
			4	417/0.254	1.524	9.9	7C	1.524	33.0	1000	305	Reel